

SPECIFICATIONS

Model		PG2900DX	PG6000DX	PG7000DX	PG6000DXS	PG7000DXS	
E N G I N E	Engine Type(YAMAHA)	MZ175L2U	MZ300L2U	MZ360L2U	MZ300L3U	MZ360L3U	
		Single Cylinder, Forced Air Cooling 4-Stroke Gasoline Engine					
	Displacement (cc)	171	301	357	301	357	
	Rated Power (ps/3600rpm)	4.5	7.9	9.7	7.9	9.7	
	Oil Volume (cc)	600	1100	1100	1100	1100	
	Ignition System	T.C.I. (Transistor Controlled Ignition)					
	Fuel	Unleaded Gasoline					
Starting System	Recoil			Recoil, Electric Start			
G E N E R A T O R	AC Output	Rated Output (kVA)	2.0	4.0	5.0	4.0	5.0
		Maximum Output (kVA)	2.2	4.5	5.5	4.5	5.5
		Rated Voltage (V)	220				
		Rated Frequency (Hz)	50				
	DC Output (V-A)	12V-8.3A					
O T H E R S	Fuel Tank Capacity (L)	18	25	25	25	25	
	Length (mm)	590	690	690	690	690	
	Width (mm)	434	550	550	550	550	
	Height (mm)	478	560	560	560	560	
	Net Weight (kg)	45	77	79	82	85	
	Continuing Time (hr)	16	10	9	10	9	
	A V R	○	○	○	○	○	
	Oil Warning System	○	○	○	○	○	
	Battery Holder	—	—	—	○	○	

Automatic Voltage Regulator (AVR)

PACIFIC's AVR smoothes the fluctuating power output and enables the operation of sensitive electronic equipment.

Oil Warning System

PACIFIC's answer to expensive repair bills. The warning system will automatically stop the engine when the oil drops below a predetermined level.

Large Fuel Tank


Large Capacity Fuel Tank with Fuel Meter.

DC Output Capability

Direct current output allows battery recharge.

Rugged Full-Frame

Its protective frame guards the generator from rough handling and damage, and also makes it easy for transport.



MULTILINE ENGINEERING CO.

UAN: 042-111-966-966

www.multiline.com.pk

E-mail: sales@multiline.com.pk

202-Y, 1st & 2nd Floor, Commercial Area, D.H.A. Lahore Cantt. Pakistan. Fax: 0092-42-589-3744